



**Product:** [GMTTD24](#) 

Outdoor Tactical tight buffered (core bonded design) PUR jacket 24f MM OM3.

## Product Description

Outdoor Tactical tight buffered optical fiber cable with core bonded design with Polyurethane (PUR) outer jacket. 24 fibers MM OM3.

## Technical Specifications

### Product Overview

Suitable Applications:	For outdoor and indoor use. These metal-free mobile cables have been designed for de-spooling and re-spooling repeatedly. Support all computer network applications such as FDDI, Gigabit Ethernet and ATM Easy to install. Not Recommended for direct burial. Core-bonded Polyurethane jacket providing simple installation.
------------------------	---

### Fiber Specifications

Fiber Type:	OM3
Fiber Buffer Material:	Nylon
Fiber Buffer Construction:	Tight
Fiber Buffer Diameter:	0.9 mm
Fiber Count:	24
Fiber Color Coding:	TIA coding (Gxxxxx.T): Blue, Orange, Green, Brown, Gray, White, Red, Black, Yellow, Violet, Pink, Aqua. With Ringmark: BL, OR, GR, BR, GY, WT, RD, BK, YL, VT, PK, AQ

### Cable Construction

Cable Core Water Blocking:	Waterblocking Aramid Yarns
----------------------------	----------------------------

### Outer Jacket Specifications

Jacket Material:	PUR - Polyurethane
Nom. Diameter:	8.5 mm (0.33 in)

### Optical Characteristics

Wavelength	850 nm	1300 nm
Max. Attenuation	2.9 dB/km	0.9 dB/km

### Mechanical Characteristics

#### Mechanical Tests

Description	Tested Standard	Requirement/Value	According to Family Specification
Cable Min. Bend Radius Installation (Short Term)	IEC 60794-1-21-E6	68 mm	
Cable Min. Bend Radius Operation (Long Term)	IEC 60794-1-21-E11	34 mm	
Cable Max. Tensile Strength Installation (Short Term)	IEC 60794-1-21-E1	2250 N (506 lbf)	
Cable Max. Tensile Strength Operation (Long Term)		750 N (170 lbf)	
Cable Max. Crush Resistance Installation (Short Term)	IEC 60794-1-21-E3	5 kN/m	IEC 60794-2-20
Cable Max. Crush Resistance Operation (Long Term)	IEC 60794-1-21-E3	3 kN/m	IEC 60794-2-20

Bulk Cable Weight:	71 kg/km (48 lbs/1000ft)
--------------------	--------------------------

### Temperature Range

Installation Temperature Range:	-5 °C to +50 °C
Operating Temperature Range:	-70 °C to +85 °C

Storage Temperature Range:	-70 °C to +85 °C
----------------------------	------------------

## Standards and Compliance

Environmental Suitability:	Indoor/Outdoor
Flammability / Reaction to Fire:	IEC 60332-1-2
ISO/IEC Compliance:	IEC 60794/ISO/IEC 11801-1

## History

Update and Revision:	Revision Number: 0.158 Revision Date: 09-26-2025
----------------------	--

## Part Numbers

### Variants

Item #	Color	Putup Type	Length	EAN
GMTTD24.002100	Black	Reel	2,100 m	8719605176790

© 2026 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.