

Large Area Infrared Transmitter with Modulator

Our two-channel Large Area Infrared Transmitter with Modulator combines an infrared modulator and transmitter, generating a wide exit angle for the infrared signal while providing a sleek and compact design that eliminates the need for rack space. It is ideal for use in large environments.

Transmissions are at a bandwidth of 2.3MHz and 2.8MHz. In 1-channel mode, the transmitter supplies areas of up to 900m². Additional transmitters allow the receiving range to be increased.

A wall and ceiling mounting kit is included.

contacta [|]

IR-TX4

Applications

For use in any situation where infrared systems can provide multiple listeners with clear sound:

- Conference and Meeting Rooms
- Cinemas and Theatres
- Courts
- Lecture Halls, Schools and Universities
- Places of Worship

Components

- Large Area Infrared Transmitter with Modulator
- Wall/Ceiling Mounting Kit

Accessories

- Portable Infrared Receiver [IR-RX2]
- Portable Infrared Underchin Receiver [IR-RXU]

Talk to us now: +44 (0) 1732 223900 (UK & ROW) +1 616 392 3400 (US & Canada) www.contacta.co.uk

Physical Data

| Dimensions | Height – 327mm (12.8") Width – 412mm (16.2") Depth – 75mm (2.95") |
|------------|---|
| Weight | 1.1kg (2.42lbs) |
| Finish | Black |



Technical Data

| Power Supply | Primary: 210 - 240V~ 50-60Hz Secondary: 28V DC |
|-------------------------------------|--|
| DC Input | Low-voltage connector, 28V DC, centre contact »negative« |
| Power Consumption | 700mA |
| Carrier Frequencies | 2.3 MHz (A-channel) and 2.8 MHz (B-channel) |
| Coverage Area | 900m² (closed room) |
| Audio Inputs | Cinch (RCA) for left and right and/or A and B-channel |
| Microphone Input | 6.3mm stereo-jack plug |
| Input Impedance | Audio-In: 18kΩ |
| | Mic-In: 1.3kΩ |
| Trigger Voltage of Audio-In | 110mV |
| Input Level Display Mic-In | 1.5mV |
| Inputs/Outputs for Combined Mode | Sync-in/Sync-Out Cinch (RCA) for left & right and/or A and B-channel |
| Display | Input level-LEDs, one per channel. |
| Ambient Conditions | 0 – +40 °C ambient temperature (non-condensing, non-corrosive environment) |
| Mounting Types | Wall or ceiling mounting kit included |

Rear Connections



Talk to us now: +44 (0) 1732 223900 (UK & ROW) +1 616 392 3400 (US & Canada) www.contacta.co.uk