



## Flush Hearing Loop for Door Entry Systems

IL-EL42-PF

Our flush hearing loop for use with door entry systems provides clear audio for hearing aid wearers.

### Features

- AGC (Automatic Gain Control) self adjusts to accommodate variations in input level
- Constant-current loop drive
- Ohmically isolated audio line input
- LED status indication – internal indicators display drive and loop fault conditions
- Frequency response compliant with IEC 60118-4 (in correct installations)
- Low power consumption

### Physical Data

Dimensions	Face Plate: Height – 140mm (5.51") Width – 140mm (5.51") Depth – 3mm (0.11")
	Back Box: Height – 110mm (4.33") Width – 110mm (4.33") Depth – 42mm (1.65")
Weight	218g (0.48lbs)
Construction	Acrylic Capped ABS
Finish	Faux Metallic Sheen

### Technical Data

Power Supply	Powered using a host system (12-24V DC) or a Contacta PS-55-01
--------------	--

### Applications

This module will accept input signals from the following:

- Pre-recorded sound sources (line out signals)
- Low voltage loudspeaker outputs
- VOIP (voice over internet protocol) audio adapters
- Intercom systems
- PA systems

Talk to us now:  
+44 (0) 1732 223900 (UK & ROW)  
+1 616 392 3400 (US & Canada)  
[www.contacta.co.uk](http://www.contacta.co.uk)

