



Portable 1 to 1 Loop

IL-PL20-2

Our Portable Loop is a versatile solution, providing mobile desktop assistance for your customers. It can be moved between rooms as required and is used in small rooms where conversation between two people takes place.

The single control unit is constructed in robust ABS plastic and incorporates a microphone, amplifier, hearing loop aerial and rechargeable battery system.

Features

- Advanced audio processing features AGC, compression, and noise gate
- Constant-current loop drive
- LED indicator shows loop drive and battery/charge status
- Magnetic field strength distance to approx 1.2metres

Standards

- CE, ROHS and WEEE compliant
- BS EN 60118-4, in correct installations

Applications

For use in any situation where one to one communication takes place at a counter, booth or desk, such as in:

- Banks
- Post offices
- Supermarkets
- Theatres
- Information centres
- Airports

Talk to us now:

+44 (0) 1732 223900 (UK & ROW)

+1 616 392 3400 (US & Canada)

www.contacta.co.uk



Physical Data

Dimensions	Height – 250mm (9.84") Width – 275mm (10.83") Depth – 110mm (4.33")
Weight	0.8kg (1.76lbs)
Construction/ Finish	Black ABS Plastic

Technical Data

Internal Battery	NiMH battery pack	Battery life approximately 4 hours
PSU	Power supply	18 VDC
Microphone	-	Electret capsule
Power and Status	Power and status LED Indication	Green/red LED
Protection	-	Self-resetting polyfuses, multiple on chip thermal shutdown
External Audio In	Connection	Boundary microphone or SCART Lead
DC Power	Connection	2.1mm DC jack