



DN-700CB Network CD/Media Bluetooth Player

Key Features:

Media player with Network and RS-232C control Intuitive Web Browser and Infrared user interface File playback from CD, USB, Network Audio, Bluetooth and AUX Tempo control for CD and USB 10-track hot start buttons for CD, USB and NET playback Two Bluetooth antennas included

Overview:

The DN-700CB is a highly-versatile media player with the added functionality of RS-232C and full network control. The DN-700CB plays files from CD, USB, Bluetooth-enabled devices and files on a local network - along with a 3.5mm AUX input for connecting external playback devices. Perfect for retail, house-of-worship, education and hotel/conference applications, its intuitive web-based interface gives the user full control of the DN-700CB from setup menus and transport control to hot-start playback.

Specifications:

System: Media player

Compatible Media: CD

3.5mm auxiliary device

Type A USB device (mass storage class)
Network-connected device (via Ethernet port)

Bluetooth audio

Supported Device

Formats, File Systems: CD: CD-DA, CD-ROM (ISO9660), CD-R

USB: FAT16, FAT32

Supported File Formats

(CDs, USB devices &

network devices) CD-DA: Sample rate: 44.1/48kHz

Bit rate: 16/24 bit File extension: .cda

WAV: Sample rate: 44.1/48kHz

Bit rate: 16/24 bit Format: stereo/mono

File extension: .wav

MP3: Sample rate: 44.1kHz

Bit rate: 32 kbps to 320 kbps, CBR and VBR

Format: MPEG1 Audio Layer 3

File extension: .mp3

Number of Channels: 2 (stereo) Audio Frequency Range: 10 Hz - 20 kHz ($\pm 1.0 \text{db}$) Signal-to-Noise Ratio: > 90 dB (A-weighted)

Total Harmonic Distortion: < 0.01% Dynamic Range: > 85dB Channel Separation: > 80dB



79-7207 DENON DN-700CB MEDIA PLAYER CD/USB/Bluetooth/Networked, XLR/RCA output, 1U

Bluetooth:

Bluetooth Version: 4.0
Output Class: Class 2

Supported Bluetooth

Profiles: A2DP, AVRCP (1.3/1.4)

Supported Bluetooth

Codecs: SBC, MP3 Bluetooth Range: 82 ft. / 25 m

Outputs:

Analogue Out: RCA L/R (unbalanced)

Load impedance: $> 10 \text{ k}\Omega$

Output level: 2 Vrms @ 10 kΩ load

Analog Out: XLR L/R (balanced)

Load impedance: $> 10 \text{ k}\Omega$ Output level: +4 dBu

Inputs:

Aux in: 1/8" (3.5mm) TRS jack socket

Input Impedance: $> 10 \text{ k}\Omega$ Maximum input level: 1 Vrms

Remote Control: Hand remote Included

Infrared protocol: NEC format Transmit output level: > 200mVp-p

Serial Remote: D-sub 9-pin Female:

Protocol: RS-232C Mode: Full Duplex

Baud Rate: 9600/38400/115200 b/s

Data: 8 bits (Start Bit: 1 bit; Stop Bit: 1 bit)
Parity: None; Flow Control: None

IP Control:

Web API: HTTP

Other / General File Folder Limits

Storage capacity: up to 2TB File size: up to 2GB

File name length: up to 255 characters
Number of files: up to 999 (for 1 folder)

Number of folders: up to 999 folders (including the root directory)

Number of folder levels: up to 8 (including the root directory)

Folder name length: up to 255 characters

Power: 100-230 VAC, 50/60 Hz; Power consumption: < 30W

Environmental Conditions:

Operating temperature: 41 - 95°F (5 -35°C)

Operating humidity: 25 - 85%, no condensation

Dimensions (WxDxH) 18.98" x 1.69" x 7.87" (482 x 43 x 200mm) with rack ears

16.93" x 1.69" x 7.87" (430 x 43 x 200mm) without rack ears

Weight: 5.5 lb (2.5 kg)

