

TECHNICAL DATA SHEET

LECTERN ACTIVE: AMPLIFIED LECTERN WITH BUILT-IN SPEAKERS



KEY FEATURES

- Powered lectern with built-in 2-way speaker column
- · Gooseneck microphone with XLR base
- RCA line and 3.5mm playback inputs
- XLR line output
- USB charging sockets
- AC convenience outlets

OVERVIEW

The Lectern Active is a portable lectern for multi-media presentations - perfect for hotels, churches, conference rooms and convention centers. This all-in-one solution is designed with professional features, such as a powerful 2-way speaker system, inputs for a microphone and playback device, and a separate output to feed an external sound system or remote zone. It also features a rigid laptop tray, a two-tier shelf system for presentation materials, and AC convenience outlets.

Inputs

- (I) XLR microphone input
- (1) 1/8" (3.5 mm) stereo input
- (I) RCA stereo input pair (line-level)

Outputs

- (I) XLR output
- (2) 5V USB Type-A charging ports
- (2) I 10 VAC convenience outlets

General

- Input Voltage 100–120/220–240 V, 50/60 Hz, 1080 W
- Fuse 100-120 V:T12.5AL 250V / 220-240 V:T6.3AL 250V
- Dimensions: 24.8 \times 15.0 \times 47.0 inches (63.1 \times 38.1 \times 1194.8 cm)
- Weight: 44.00 lbs. (19.96 kg)

SPECIFICATIONS

System

- 100W RMS (200W Peak) Class-D amplifier
- · Bi-amp design
- (4) 5.25" full-range speakers
- (1) Horn-loaded HF driver
- · Precision electronic crossover and limiter
- 2-channel audio mixer

Controls

- Mute button
- Microphone volume
- Auxiliary volume for 1/8" (3.5 mm) and RCA aux inputs

