Product Information Sheet

NEUTRIK NMJ2HC-S JACK SOCKET

43-201NEUTRIK NMJ2HC-S JACK SOCKET



DESCRIPTION

1/4" mono jack, un-switched, with chrome ferrule and standard solder lugs, mounting nut included.

FEATURES & BENEFITS

- Wide body and extremely durable contacts
- Mates with all mono A-gauge plugs acc. EIA RS-453 standard

TECHNICAL SPECIFICATION

Product	
Title	NMJ2HC-S
Connection	Jack
Gender	female
Electrical	
Contact resistance	< 15 mΩ (inner)
Dielectric strength	1 kVdc
Insulation resistance	≥ 1 GΩ @ 500 V dc
Rated current per contact	3 A
Mechanical	
Insertion force	< 20 N
Withdrawal force	7 N
Lifetime	> 10000 mating cycles
Panel thickness	< 4.7 mm
Wiring	Solder lugs
Locking device	Retention spring
Mounting direction	rear
Chassis shape	11.4 mm

Material	
Cap / Nut / Washer	PA 6.6 15% GR
Contact plating	2 µm Ni
Contacts	Bronze (CuSn6)
Shell	Polyamide (PA 6.6 15 % GR)
Environmental	
Standard compliance	EIA RS 453, IEC 60603-11
Solderability	Complies with IEC 68-2-20
Temperature range	-25 °C to +70 °C